

# iPP315

---

## The multi-payment PIN Pad that simplifies checkouts

---

- Secure payment acceptance at checkout
- Accepts EMV, magstripe and NFC/  
contactless payments quickly and easily
- Connects with Ingenico Desk series  
terminals with a single USB cable



security



smartcard



magstripe



contactless



color display

The iPP315 enables secure and fast checkouts, by accepting all electronic payments, including EMV, magstripe and NFC/contactless.

#### Highest Security

The iPP315 is PCI-PTS 4.x certified and meets all security requirements. It ensures secure data and application management and enables highly secure transactions for merchants. The optional PIN privacy shield provides additional security and confidentiality for consumers for PIN entry.

#### Total Payment Flexibility

The iPP315 accepts all forms of electronic payments, including EMV, magstripe and NFC/contactless.

#### Easy Connectivity

The iPP315 easily connects with Ingenico's Desk series terminal using a single USB cable.

#### Maximum Ease of Use

Among the world's smallest and lightest devices, the iPP315 is designed for easy handling and daily use. A backlit keypad and vivid color display make PIN entry and payment operations highly visible and intuitive. Large keys and an audible buzzer simplify transactions while reducing PIN entry errors. In addition, clear visual indicators facilitate NFC/contactless payments.

#### Operating System

The iPP315 leverages Ingenico's Telium 2 platform, developed from over 30 years of experience in the payment industry. Secure, fast, fully scalable and easy to integrate, Telium 2 is the world's most reliable operating system for payment services.



NAME	iPP315	
<b>Processor</b>	ARM 9 & ARM 7	●
<b>Memory</b>	PCI 4.x version	32 MB SDRAM, 128 MB Flash
<b>Card Readers</b>	Smart card	●
	Magstripe	●
	Contactless reader	ISO 14443-4 A/B EMV contactless level 1 Mifare
<b>Display</b>	TFT Color display, 2.8" 320 x 240 QVGA	● ●
<b>Keyboard</b>	Backlit operational keys	15
	Navigation keys	4
<b>Audio</b>	Buzzer	●
<b>Terminal Connections</b>		1 USB slave
<b>Power</b>	USB powered	5V 500 mA
<b>Terminal Size</b>	(L x W x H) inches	6.61 in x 3.26 in x 1.57 in
<b>Weight</b>	Without cable	9.52 oz
<b>Environment</b>	Operating temperature	41°F to 113°F (+5°C to +45°C)
	Storage temperature	-4°F to 158°F (-20°C to +70°C)
	Relative humidity, non-condensing	85% HR to 104°F (+40°C)
<b>Accessories</b>	USB cable for connection to Desk series	Optional
	Clip-able PINshield	Optional
<b>Customization</b>	Lens marking	Optional
	Top casing	Optional
<b>Security</b>	PCI PTS 4.x	●

USA\_Datasheet\_iPP315\_IQWL\_201012. All rights reserved. This document is not binding and the specifications above can be modified without prior consent. ©2020



[www.ingenico.us](http://www.ingenico.us)

**ingenico**  
aWorldlinebrand