



www.aures.com



HSD EXCLUSIVE
by POSLIGNE®



A high-performance
PC platform for all Retail applications and environments

With compact dimensions, this POS system is sturdy, safe, reliable, long-lasting and easy to maintain, at home in both "front office" environments (*cash desk*) and in the "back office" (*where it can be used as a server for example*). Its 1.6mm-thick reinforced steel base-frame ensures optimum rigidity.

Poséo 5200 is a very flexible and upgradable system, featuring in its high end configuration an INTEL 945G + ICHR chipset, a Dual-Core processor, 4GB of DDR2 RAM and a RAID 1 controller card integrated directly onto the motherboard, plus rack-mounted Hot Swap SATA disk drives (*2nd disk optional*).

A small LCD control screen on front side of the PC enables real time display of some data related to the system status (*temperature's level, fans' rotation, power supplies' voltage, hard disk(s) drives, network interface management...*).

Poséo 5200 integrates '**HSD Exclusive**', (*Hardware Status Display*): this embedded utility, provides an instant display – on the connected touch screens - of all the key system data, in a choice of three languages (*processor temperatures, fan/cooling system status, power supply or network interface readings, HDD (RAID) status, network interface*), and so on.

This feature also allows the key status from an entire batch of Retail PCs to be centralised, automatically sending information via e-mail (*to a store chain's Information Systems Manager or Hotline*), for as many units and locations as required, for enhanced security.

When used with a touch-screen monitor such as AURES' OLC15, **Poséo 5200** functions as the nerve centre of an ultra-high performance EPOS modular system.

POSÉO 5200 performance for retail

- High performance from a compact unit: (RAID 1, HOT SWAP Sata disk drives, latest-generation processors, etc.)
- Optimum connection capabilities
- Small control display on front of the system (system's status LCD)
- HSD Exclusive : centralized management control of data for enhanced security
- Optimized for easy maintenance and long-lasting components
- Key Lock



MODEL

POSÉO 5200

Processor	Intel Dual Core E2160 (LGA 775)
Chipsets	Intel 945G + ICH7R
RAM	up to 4GB – 2 x DDR2 (2GB in standard)
SDRAM	Up to 232MB shared SDRAM

STORAGE

Hard disk drive	3.5" SATA 160GB Hot Swap disk drives (2 nd disk in option)
PCI extension bus slots	2 x PCI
RAID 1	integrated

FRONT PANEL

USB 2.0	2 x USB type A
Small control display	real time display of system's and processor's temperature levels, fans' rotation, power supply voltage, hard disk drives ventilation & network interface status, RAID controller

Key lock

REAR PORTS

USB 2.0	8 (+2 on front panel)
USB Retail	4 (1 x 5V, 2 x 12V, 1 x 24V)
Series/COM	5 self powered
DVI Port	1
VGA	1 x DB 15F
Audio output	1
10/100/1000 LAN	1
Parallel (printer)	1 x DB 25F
24V port	1 (receipt printer)
12V port	1 (VFD customer display)
Cashdrawer ports	1 x RJ 11 (12V / 24V)
Keyboard	1 x PS2

ENVIRONMENT

Power supply	integrated 230W
Voltage	100-240 V, 50-60 Hz
Safety / EMC	FCC Class A / CE / LVD
Operating temperature	+5° / +35°C
Storage temperature	-10° / +60°C
Humidity rating (in operation)	20% ~ 85% (RH without condensation)
Humidity rating (in storage)	5% ~ 90% (RH without condensation)
Dimensions (W x D x H)	270 x 345 x 120mm
Weight	7kg net
Operating systems	POSReady, Windows XP Pro, Windows 7, Linux

OPTIONS

CD/DVD reader	
2 nd hard disk – increased RAM	



Specifications are subject to change without notice

www.aures.com

MANUFACTURER OF REMARKABLY
DIFFERENT EPOS TERMINALS

HOT
SWAP

RAID 1

AURES