



## Verifone V240m

The V240m, part of the Verifone Engage portfolio, combines the latest in features, functionality, and performance into one efficient and cost-effective solution.

Boasting a large, 3.5" color touch display, more memory, faster processor and multiple connectivity options, this full-function portable payment device makes doing business on the go easy. Whether merchants are looking to accept basic payment transactions or explore more advanced capabilities like paying with points, digital couponing, and other value-added services, the V240m makes it possible. Ideal for pay-at-the table, curbside delivery, kiosks and line-busting.

- New, intuitive user interface makes it easy to navigate
- Corning® Gorilla® Glass 3 technology minimizes screen scratches and breakage
- EMV-ready and fully compliant with the latest PCI 5.0 requirements
- Accepts all payment types: NFC/contactless, mobile wallets, EMV, magstripe
- Supports a variety of apps with Verifone's App Marketplace

## Specifications

### Processor

600 MHz, Cortex A9 32-bit RISC processor, 1500 MIPS

*\*Enhanced Commerce option includes graphic accelerator*

### Memory

384MB (256MB Flash, 128MB SDRAM, micro-SD)

*\*Enhanced Commerce option: 1024MB (512MB Flash, 512MB SDRAM, micro-SD)*

### Display

3.5" HVGA capacitive touch screen, Corning® Gorilla® Glass 3 technology

### Operating System

V/OS (Linux-based)

### Connectivity

GPRS or 3G and/or Bluetooth 4.2 + WiFi

*\*Enhanced Commerce option includes 5GHz and 2.4GHz WiFi*

### Printer

30 lps, 40mm paper roll

### Card Readers

Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved

### Contactless

ISO14443 A&B, MiFare, ISO18092-capable, EMVCo L1 certification, supports major NFC/contactless schemes

### Peripheral Ports

Single USB connector for 1 host/client, separate charging connector

### Audio

Buzzer

*\*Enhanced Commerce option includes speaker*

### Security

PCI PTS 5.X-approved

### Power

Battery: 3.7V/2450mAh Li-ion; PSU: 100-240 VAC w/ output DC 5V, 1 amp

### Environmental

Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing

### Physical

162.9mm L x 75.3mm W x 53.4mm H

### Base

- Charge-only base
- Full-featured base: powered RS-232, dial-up, Ethernet, USB client, USB host, Bluetooth

### Other Standard Features

2 SAM slots, geolocation, backlit keypad, uSD memory slot, dual SIM

### Options/Accessories

Privacy shield